

Asset GPS Tracker



Over 4 years long standby time

Inbuilt high capacity battery which ensures remarkably power efficient.

Magnetic installation


Contain two industrial magnets which facilitates it attach to flat metal surface.

IP66 water resistant

Hard and rugged enclosure guarantees it complete shockproof and durable.

Multiple alerts & reports

Support speeding/drop/geo-fence alerts, cornering/heartbeat reports etc.



APPLICATION



Container



Ship



Valuables



Vehicle

SPECIFICATIONS

ITEM	PARAMETER	SPECIFICATIONS
Outer case	Dimension	105 mm x 75 mm x 45 mm
	Material	ABS
	Water resistance	IP66
Power consumption	Working voltage	3.7 V
	Average current	50 mA
	Current in standby mode	50 uA
	Internal battery	7400 mAh/3.7 V
	Working hour	Consecutive working hours: > 120 hours A piece of data per day: > 2 years Standby time: > 4 years (Ambient temperature: 20°C)
I/O port	1-Wire interface (optional)	1
	A/D interface (optional)	1
GSM	Frequency band	850/900/1800/1900 MHz
	Antenna	Internal antenna
GPS	Positioning accuracy	2.5 meters
	GPS sensitivity	-162 dBm
	Positioning time	Cold start: < 42 seconds
		Hot start: < 3 seconds
	Recapture time: < 2 seconds	
Satellite receiving channel	56 channels	
Antenna	Internal/External antenna	
Ambient environment	Operating temperature	-15°C to 65°C
	Storage temperature	-25°C to 70°C
	Operating humidity	5%–95% non-condensing
Weight	322g	
Sensor	Built-in 3-axis accelerometer (used to determine movement, stillness, and vibration.)	
Memory	8 MB buffer (Store up to 8,192 GPRS cache records and 100 SMS cache records)	
LED indicator	LED indicators showing power, GPS, and GSM status	



ACCESSORIES

- T355 Tracker
- Travel adapter
- Mini USB cable
- Switch sticker
- CD download card



OPTIONAL ACCESSORIES

External GPS antenna



RoHS



+86(755)83462818



www.meitrack.com



info@meitrack.com



6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd., Futian Free Trade Zone, Shenzhen, China. 518038