



- Compact Size
- Multiple I/O Interfaces
- 1-wire Interface
- Scheduled Timing Report
- Geo-fences
- Motion Detection
- Driving Behavior Monitoring
- Crash Detection
- Power Supply Monitoring
- Tow Alarm
- Fuel Level Monitoring
- Temperature Monitoring
- Driver ID Identify
- Support Virtual Odometer

GV65 Series

Compact multi-interface GNSS trackers for a wide range of vehicle tracking applications

- 56g (GV65)
62g (GV65 Plus)
- 30°C ~ +80°C

- 73mm(L) × 54mm(W) × 22.7mm(H)
- Operating Voltage: 8V to 32V DC
Li-Polymer, 250 mAh (GV65 Plus)

The GV65 series includes two compact GNSS trackers designed for a wide variety of vehicle tracking applications. The series includes multiple digital/analog I/Os that can be used for monitoring or controlling external devices, and has a 1-wire interface for iButton driver ID or temperature monitoring.



GV65 Series Models

	Region	Operating Band	GNSS Type	Position Accuracy (CEP)	Backup Battery	Certificate
GV65	Worldwide	GSM 850/900/1800/1900 MHz	u-blox All-in-One GNSS receiver	Autonomous: < 2.5m	N/A	CE/E-Mark
GV65 Plus	Worldwide	GSM 850/900/1800/1900 MHz	u-blox All-in-One GNSS receiver	Autonomous: < 2.5m	Li-Polimer, 250 mAh	CE

Interfaces



Digital Inputs	1 positive trigger input for ignition detection 2 negative trigger inputs for normal use
Digital Output	1 digital output, open drain, 150 mA max drive current
Latched Digital Output	1 digital output with internal latch circuit, open drain, 150 mA max drive current
Analog Input	1 analogue input with selectable input voltage range (0V-12V or 0V-30V)
1-wire Interface	Support 1-wire temperature sensor and iButton driver ID
GSM Antenna	Internal only
GNSS Antenna	Internal antenna and optional external antenna
LED Indicators	CEL, GNSS, PWR
Mini USB Interface	Used for upgrading and debugging